



LED Wall Pack Series
20 Watt – 120Vac
Model #: RL-WP20-S (straight)
RL-WP20-A (arched)


Maintenance free outdoor 20 watt LED wall pack. High quality aluminum alloy housing with corrosion resistive coating, complete with stainless steel bolts and screws. Photo cell, tempered glass lens with rubber gasket. Replaces the equivalent of a 70 watt HPS. Energy savings of up to 70% when compared to equivalent incandescent lighting. IP54 for wet locations.

Multiple Applications

Ideal for:

- Medium area lighting;
- Security Lighting

Specifications

Model Number	RL-WP20-S, RL-WP20-A
Input Voltage	100-277 Vac, 50-60 Hz
Input Current	0.5A @100V / 0.2A @277V
Power Consumption	22W, PF≥0.95
LED Chip	14pc Cree XBD 110 LM/W
Lumen Output	1400 lm
Luminous Efficiency	65 lm/w
Color Temperature	Natural White (4100K)
Color Rendering Index (CRI)	>70
Beam Angle	120°
Estimated Lifespan	50,000 hours
Driver	Meanwell
Driver Output Voltage	12 Vdc
Driver Output Current	1200 mA
Operating Temperature	-20°C to +40°C
Materials	Coated Aluminum Alloy, Polycarbonate & Stainless Steel
IP Rating	IP54 (suitable for wet locations)
Certifications	 (E359673), CE, RoHS
Color of Lamp Housing	Brown
Dimensions (W x H x D -See Line Diagram)	175.73 mm x 279.73 mm x 129.25 mm
Weight	3.18 kg
Warranty*	3 years

* Details of our warranty information are available at www.RhynoLED.ca/warranty

All information contained within this documentation was derived from information and tests Rhyno LED Lighting Solutions Inc believes to be accurate and reliable; however, the accuracy and/or completeness of the information relied upon cannot be guaranteed. As the use and conditions of use are beyond the control of Rhyno LED Lighting Solution Inc, the purchaser/end user must determine the suitability of the product for the intended use and assumes all risk and liability.

Your Imagination Is Your Only Limitation